

18" Depth, 6" High	MODEL Stainless	MODEL (Choose Color)
660± CFM @ 1.5 to 4.6 Sones 7" Round Duct	N1930BPSB-SS N1936BPSB-SS N1942BPSB-SS N1948BPSB-SS	N1930BPSB-BL or WH N1936BPSB-BL or WH N1942BPSB-BL or WH N1948BPSB-BL or WH
790± CFM @ 1.5 to 4.6 Sones 8" Round Transition	N1930BPSB-8-SS N1936BPSB-8-SS N1942BPSB-8-SS N1948BPSB-8-SS	N1930BPSB-8-BL or WH N1936BPSB-8-BL or WH N1942BPSB-8-BL or WH N1948BPSB-8-BL or WH




FEATURES:

- 304 Marine Grade Stainless Steel.
- Variable Controls.
- Filters: Slim Baffle
- Center Panel Lighting: LED bulb included.
- Heat Controlled Thermostat, Fire Safety Controlled. Activates at 130 degrees.
- Electrical: 115 AC, 60 Hz, 9 Amps. For proper installation, unit must be hard wired. Suggested use with 15 Amp Circuit.
- Suggested Distance Code: 36" above cooking surface.

OPTIONS:

- Matte Black, additional charge.
Ex: N1930BPSB-MB (Matte Black)
- Remote wiring, see accessories.

NO Returns on Matte or RAL colors.



Example: N1930BPSB-8-SS
Vent Size 8" Round x 3-1/2" High



SEVEN YEAR, IN HOME, LIMITED WARRANTY, THE BEST IN THE INDUSTRY!

All dimensions are (+/-) 1/16" and are subject to change. Drawings are not to scale.